

Druckluftwerkzeuge | Druckluftmotoren

- safety lever start
- can be used without lubrication
- integrated silencer
- ergonomic handle
- versatile in usage
- rotation direction can be reverse easily by pulling machine



Your contact person

Mr. Export Team

✉ export@mannesmann-demag.com

Technical Data

Type	MAY 10
Article Nr.	136309028
Start	Lever start
Free speed	450 min ⁻¹
Free Speed counter clockwise	930 min ⁻¹
Power	- Watt
Square shaft clamping range	-
Cutting n stell up to	M 10 mm
Cutting in light alloy up to	M 13 mm
Diameter	46.00 mm
Length	335.0 mm
Noise level	78 dB(A)
Weight without hose	1.82 kg
Air consumption	11.0 ls
Hose I.D.	8.0 mm
Connection thread	G 1/4" i
Accessories supplied	Quickchange chuck for tap holder, sidewise handhold, pendant

All data related to 6.3 bar working pressure.
Subject to technical alterations.

Accessories

Type	Article Nr.
Quick change chuck for tap holder	659611001
Tap holder for shank M 2 - 2,8 mm ; driv. square end: 2,1	655211028
Tap holder for shank M 3 - 3,5mm ; driv. square end: 2,7	655271035
Tap holder for shank M 3,5 - 4,0 mm ; driv. square end: 3,0	655301040
Tap holder for shank M 4 - 4,5 mm ; driv. square end: 3,4	655341045
Tap holder for shank M 5/6/8 - 6,0 mm ; driv. square end: 4,9	655491060
Tap holder for shank M 10 - 7,0 mm ; driv. square end: 5,5	655551070
Tap holder for shank M 11 - 8,0 mm ; driv. square end: 6,2	655621080
Tap holder for shank M 12 - 9,0 mm ; driv. square end: 7,0	655701090
Tap holder for shank M 12 - 9,0 mm ; driv. square end: 7,0	655901110